

RIGID HYDRAULIC PIPE STAINLESS STEEL



STANDARD

EN 10305-4, ASTM-A 269 / A 213

MATERIAL

Acero Inoxidable AISI 316-L.

NOTES

Se sirven barras de 6m. Presiones de trabajo (factor 4:1).

| Code | Ø ext mm | Espesor mm | P.trabajo bar | Peso kg/m |
|-------------|----------|------------|---------------|-----------|
| XRU31600610 | 6 | 1 | 490 | 0,125 |
| XRU31600615 | 6 | 1,5 | 735 | 0,169 |
| XRU31600810 | 8 | 1 | 368 | 0,175 |
| XRU31600815 | 8 | 1,5 | 551 | 0,244 |
| XRU31601010 | 10 | 1 | 294 | 0,225 |
| XRU31601015 | 10 | 1,5 | 441 | 0,318 |
| XRU31601020 | 10 | 2 | 588 | 0,401 |
| XRU31601210 | 12 | 1 | 245 | 0,275 |
| XRU31601215 | 12 | 1,5 | 368 | 0,393 |
| XRU31601220 | 12 | 2 | 490 | 0,501 |
| XRU31601420 | 14 | 2 | 420 | 0,600 |
| XRU31601515 | 15 | 1,5 | 294 | 0,506 |
| XRU31601620 | 16 | 2 | 368 | 0,700 |
| XRU31601815 | 18 | 1,5 | 245 | 0,618 |
| XRU31601820 | 18 | 2 | 327 | 0,800 |
| XRU31602030 | 20 | 3 | 441 | 1,275 |

| Code | Ø ext mm | Espesor mm | P.trabajo bar | Peso kg/m |
|-------------|-------------|---------------|------------------|--------------|
| XRU31602220 | 22 | 2 | 267 | 1,000 |
| XRU31602530 | 25 | 3 | 353 | 1,650 |
| XRU31602820 | 28 | 2 | 210 | 1,302 |
| XRU31603520 | 35 | 2 | 168 | 1,653 |
| XRU31603840 | 38 | 4 | 309 | 3,355 |
| XRU31604230 | 42 | 3 | 140 | 2,003 |

The data provided is for guidance only and may be subject to changes or corrections without prior notice. Please contact us if you detect any errors or require further technical information. (Ficha generada el 02/04/2026 a las 13:57:43)

Rayflex Sistemas y Fluidos S.A.
Pol. Ind. El Pla, C/Miquel Torelló i Pagès, 37-39, 08750 Molins de Rei, Barcelona
T. + 34 93 680 43 20 - info@rayflex.net

© Rayflex Todos los derechos reservados