


SWIVEL FEMALE SAE JIC 37°



Code	Rosca	A mm	B mm	C mm	Ø manguera pulg.
RL10410403	7/16				3/16
RL10410404	7/16"-20	14.5	9.7	14	1/4
RL10410503	1/2				3/16
RL10410504	1/2"-20	15.5	9.5	17	1/4
RL10410505	1/2"-20	15.5	9.5	17	5/16
RL10410604	9/16"-18	15.5	9.5	19	1/4
RL10410605	9/16"-18	17	9.5	19	5/16
RL10410606	9/16"-18	17	9.5	19	3/8
RL10410706	5/8				3/8
RL10410805	3/4"-16				5/16
RL10410806	3/4"-16	18.5	10.7	22	3/8
RL10410808	3/4"-16	18.5	10.7	22	1/2
RL10411006	7/8				3/8
RL10411008	7/8"-14	20.5	12.5	27	1/2
RL10411010	7/8"-14	21	12.7	27	5/8
RL10411012	7/8				3/4
RL10411208	1"1/6"-12	21	14.3	32	1/2
RL10411210	1"1/6"-12	22.2	14.3	32	5/8
RL10411212	1"1/16"-12	21	13.8	32	3/4

Code	Rosca	A mm	B mm	C mm	Ø manguera pulg.
RL10411412	1"3/16				3/4
RL10411612	1"5/16-12	28.5	15.1	38	3/4
RL10411616	1"5/16"-12	26.5	16	38	1"
RL10412016	1"5/8"-12	30	16	50	1"
RL10412020	1"5/8"-12	29	16	50	1"1/4
RL10412420	1"7/8"-12	31.4	18.5	55	1"1/4
RL10412424	1"7/8"-12	31.4	18.5	55	1"1/2
RL10413232	2"1/2"-12	38	24	75	2"

The data provided is for guidance only and may be subject to changes or corrections without prior notice. Please contact us if you detect any errors or require further technical information. (Ficha generada el 02/04/2026 a las 19:39:45)

Rayflex Sistemas y Fluidos S.A.
 Pol. Ind. El Pla, C/Miquel Torelló i Pagès, 37-39, 08750 Molins de Rei, Barcelona
 T. + 34 93 680 43 20 - info@rayflex.net

© Rayflex Todos los derechos reservados