

# GAD HOSE



## APPLICATIONS

Aceites, carburantes, gasoil, refrigerantes.

## INTERNAL CORE

Caucho NBR sintético

## MAXIMUM TEMPERATURE

90

## STANDARD

DIN 73379

## COVER

Trenza téxtil

## MINIMUM TEMPERATURE

-20

Code	Galga	Ø int pulg	Ø int mm	Ø ext mm	P.trabajo bar	Protura bar	Rad. curv. mm	Peso kg/m
RT470307	2	1/8	3	7	20	80	15	0,04
RT470408		5/32	4	8	20	80	20	0,05
RT470511	3	3/16	5	11	20	80	25	0,08
RT470612	4	1/4	6	12	20	80	30	0,10
RT470713		5/16	7	13	15	60	35	0,13
RT470813	5	5/16	8	13	15	60	40	0,11
RT470916	6	3/8	9	16	15	60	45	0,14
RT471220	8	1/2	12	20	10	40	50	0,24
RT471623	10	5/8	16	23	10	30	160	0,28
RT471927	12	3/4	19	27	10	30	190	0,38
RT472533	16	1"	25	33	10	30	250	0,50

The data provided is for guidance only and may be subject to changes or corrections without prior notice. Please contact us if you detect any errors or require further technical information. (Ficha generada el 18/06/2026 a las 02:56:01)

