

# VISO HOSE (INCHES)



## APPLICATIONS

Manguera apta para aceites y diesel.

## INTERNAL CORE

Caucho NBR resistente al contenido aromático.

## MAXIMUM TEMPERATURE

90

## STANDARD

EN ISO 6806 - DIN73379

## COVER

Acero galvanizado trenzado

## MINIMUM TEMPERATURE

-20

Code	Galga	Ø int pulg	Ø int mm	Ø ext mm	P.trabajo bar	P.rotura bar	Rad. curv. mm
RT460604	4	1/4	6	11	25	75	30
RT460805	5	5/16	8	13	25	75	40
RT461006	6	3/8	10	15	25	75	50
RT461308	8	1/2	13	19	20	60	65
RT461610	10	5/8	16	22	20	60	80
RT462012	12	3/4	19	25	15	45	95
RT462516	16	1"	25	33	15	45	125

The data provided is for guidance only and may be subject to changes or corrections without prior notice. Please contact us if you detect any errors or require further technical information. (Ficha generada el 18/06/2026 a las 03:02:55)

Rayflex Sistemas y Fluidos S.A.

Pol. Ind. El Pla, C/Miquel Torelló i Pagès, 37-39, 08750 Molins de Rei, Barcelona

T. + 34 93 680 43 20 - info@rayflex.net