


REUSABLE FERRULE FOR SAE 100 R1 - R2 HOSE



MATERIAL

Acero al carbono - zincado trivalente

WORKING PRESSURE

La presión de trabajo se reducirá al 10% de la declarada (SAE J517).

MAXIMUM TEMPERATURE

80

| Code | A mm | B mm | C mm | Ø manguera pulg. |
|------------|---------|---------|---------|---------------------|
| RR70530003 | 7x0,75 | 17 | 11 | 3/16 |
| RR70530004 | 9x1 | 18 | 12,5 | 1/4 |
| RR70530005 | 11x1 | 20 | 14 | 5/16 |
| RR70530006 | 13x1 | 22 | 16,2 | 3/8 |
| RR70530008 | 5/8 UNF | 26 | 19,5 | 1/2 |
| RR70530012 | 22x1,5 | 32 | 26,5 | 3/4 |
| RR70530016 | 1"3/16 | 42 | 34,5 | 1" |
| RR70540004 | 9x1 | 19 | 14 | 1/4 |
| RR70540005 | 11x1 | 22 | 15 | 5/16 |
| RR70540006 | 13x1 | 24 | 17,5 | 3/8 |
| RR70540008 | 5/8 UNF | 27 | 20 | 1/2 |
| RR70540012 | 22x1,5 | 34 | 27,5 | 3/4 |
| RR70540016 | 1"3/16 | 45 | 36,5 | 1" |

Rayflex Sistemas y Fluidos S.A.
Pol. Ind. El Pla, C/Miquel Torelló i Pagès, 37-39, 08750 Molins de Rei, Barcelona
T. + 34 93 680 43 20 - info@rayflex.net

© Rayflex Todos los derechos reservados