

COMPRESSED AIR FOR SEVERE APPLICATIONS - 20 BAR



APPLICATIONS

Aire comprimido en aplicaciones severas.

REINFORCEMENT

Trenza téxtil de gran tenacidad.

WORKING PRESSURE

20

MINIMUM TEMPERATURE

-30

INTERNAL CORE

SBR/NBR negro

COVER

SBR negro.

MAXIMUM TEMPERATURE

80

Code	Ø int pulg	Ø int mm	Ø ext mm	Peso kg/m
TA155AA019	3/4	19	29	0,550
TA155AA025	1"	25	35	0,690
TA155AA032	1"1/4	32	44	0,880
TA155AA038	1"1/2	38	50	1,020
TA155AA040	1"9/16	40	52	1,070
TA155AA045	1"3/4	45	57	1,190
TA155AA051	2"	51	65	1,650
TA155AA060	2"3/8	60	76	2,180
TA155AA063	2"1/2	63	79	2,280
TA155AA076	3"	76	92	2,780
TA155AA102	4"	102	118	3,630

Rayflex Sistemas y Fluidos S.A.
Pol. Ind. El Pla, C/Miquel Torelló i Pagès, 37-39, 08750 Molins de Rei, Barcelona
T. + 34 93 680 43 20 - info@rayflex.net

© Rayflex Todos los derechos reservados