

LIQUID DELIVERY FOR SEVERE APPLICATIONS, COLLAPSIBLE - 10 BAR



APPLICATIONS

Impulsión de líquidos en aplicaciones severas. Drenaje de pozos y uso general.

REINFORCEMENT

Trenza téxtil de gran tenacidad.

WORKING PRESSURE

10

MINIMUM TEMPERATURE

-30

INTERNAL CORE

EPDM negro.

COVER

EPDM negro.

MAXIMUM TEMPERATURE

80

| Code | Ø int pulg | Ø int mm | Ø ext mm | Peso kg/m |
|------------|---------------|-------------|-------------|--------------|
| TA253AA032 | 1"1/4 | 32 | 40 | 0,460 |
| TA253AA038 | 1"1/2 | 38 | 46 | 0,540 |
| TA253AA040 | 1"9/16 | 40 | 48 | 0,570 |
| TA253AA045 | 1"3/4 | 45 | 53 | 0,660 |
| TA253AA051 | 2" | 51 | 59 | 0,730 |
| TA253AA060 | 2"3/8 | 60 | 68 | 0,860 |
| TA253AA063 | 2"1/2 | 63 | 71 | 0,890 |
| TA253AA076 | 3" | 76 | 84 | 1,280 |

The data provided is for guidance only and may be subject to changes or corrections without prior notice. Please contact us if you detect any errors or require further technical information. (Ficha generada el 02/04/2026 a las 08:06:43)

