

Soft-Sealing Cutting Ring
 Type FI-WDDS • Series L / S


B

Series	Tube OD mm	PN bar	Dimensions mm		Weight kgca. per 100	Ordering Codes Soft-Sealing Cutting Ring
			D1	L1		
L	6	500	8,8		0,19	FI-WDDS-06L/S-V-W3
	8	500	8,8		0,24	FI-WDDS-08L/S-V-W3
	10	500	9,8		0,35	FI-WDDS-10L/S-V-W3
	12	400	9,8		0,41	FI-WDDS-12L/S-V-W3
	15	400	10,2		0,66	FI-WDDS-15L-V-W3
	18	400	10,2		0,82	FI-WDDS-18L-V-W3
	22	250	11,5		1,06	FI-WDDS-22L-V-W3
	28	250	11,5		1,28	FI-WDDS-28L-V-W3
	35	250	13,5		2,36	FI-WDDS-35L-V-W3
	42	250	13,5		2,75	FI-WDDS-42L-V-W3
	S	6	800	8,8		0,19
8		800	8,8		0,24	FI-WDDS-08L/S-V-W3
10		800	9,8		0,35	FI-WDDS-10L/S-V-W3
12		630	9,8		0,41	FI-WDDS-12L/S-V-W3
14		630	10,2		0,73	FI-WDDS-14S-V-W3
16		630	10,3		0,83	FI-WDDS-16S-V-W3
20		420	12,5		1,28	FI-WDDS-20S-V-W3
25		420	12,5		1,58	FI-WDDS-25S-V-W3
30		420	13,5		2,41	FI-WDDS-30S-V-W3
38		420	13,5		3,00	FI-WDDS-38S-V-W3

Ordering Codes

***FI-WDDS*-15*L*-V*-W3**

* Soft-Sealing Cutting Ring		FI-WDDS
* Outside Tube Diameter D1 (in mm)		-15
* Series	Light Series	L
	Heavy Series	S
* Seal Material	FKM (Viton®)	-V
* Material Code	Steel, zinc/nickel-plated	-W3

Please contact STAUFF for alternative materials and surface finishings.

Standard seal material is FKM (Viton®).