
Straight Fitting with 24° Taper / O-Ring
Type FI-SNV ▪ Series L





Ordering Codes

***FI-SNV*-10*L*-V*-W3*-DKO**

* Straight Fitting with 24° Taper / O-Ring (DKO)		**FI-SNV**
* Outside Tube Diameter D1 (in mm)		**-10**
* Series	Light Series (page 138)	**L**
	Heavy Series (page 139)	**S**
* Seal Material	FKM (Viton®)	**-V**
* Material Code	Steel, zinc/nickel-plated	**-W3**
	Please contact STAUFF for alternative materials and surface finishings.	
* Assembling / Kitting	Fitting body supplied with swivel nuts and O-rings	**-DKO**
* Total length	dimension see table	**-GLA**
	dimension see table	**-GLB**

Spare Parts / Accessories




O-Ring
Type **O-RING** Page 239

Series	Tube OD mm D1	PN bar	Dimensions mm D2	L1	L2	S1	Weight kg ca. per 100	Ordering Codes
L	6	500	3	30,8	33,5	14	2,81	FI-SNV-06L-V-W3-DKO-GLB
	6	500	3	34	36,7	14	3,82	FI-SNV-06L-V-W3-DKO
	6	500	3	36,3	39	14	2,99	FI-SNV-06L-V-W3-DKO-GLA
	8	500	5	30,8	33,5	17	4,19	FI-SNV-08L-V-W3-DKO-GLB
	8	500	5	34	36,7	17	4,29	FI-SNV-08L-V-W3-DKO
	8	500	5	36,8	39,5	17	4,45	FI-SNV-08L-V-W3-DKO-GLA
	10	500	6	32,2	34	19	5,56	FI-SNV-10L-V-W3-DKO-GLB
	10	500	6	36	37,8	19	5,78	FI-SNV-10L-V-W3-DKO
	10	500	6	37,7	39,5	19	6	FI-SNV-10L-V-W3-DKO-GLA
	12	400	8	32,2	34	22	7,5	FI-SNV-12L-V-W3-DKO-GLB
	12	400	8	36	37,8	22	7	FI-SNV-12L-V-W3-DKO
	12	400	8	39,5	41,3	22	8,04	FI-SNV-12L-V-W3-DKO-GLA
	15	400	11	39	40,8	27	12,58	FI-SNV-15L-V-W3-DKO
	15	400	11	40,7	42,5	27	12,62	FI-SNV-15L-V-W3-DKO-GLA
	18	400	13	36,2	39	32	17	FI-SNV-18L-V-W3-DKO-GLB
	18	400	13	40,5	43,3	32	17,59	FI-SNV-18L-V-W3-DKO
	18	400	13	42,2	45	32	18,16	FI-SNV-18L-V-W3-DKO-GLA
	22	250	17	41,2	44	36	24,12	FI-SNV-22L-V-W3-DKO-GLB
	22	250	17	45	47,8	36	24,91	FI-SNV-22L-V-W3-DKO
	22	250	17	46,7	49,5	36	25,4	FI-SNV-22L-V-W3-DKO-GLA
	28	250	23	46	48,8	41	27,4	FI-SNV-28L-V-W3-DKO
	28	250	23	48,7	51,5	41	28,57	FI-SNV-28L-V-W3-DKO-GLA
	35	250	28	46	52	50	43,36	FI-SNV-35L-V-W3-DKO-GLB
	35	250	28	53	59	50	45,98	FI-SNV-35L-V-W3-DKO
	35	250	28	55	61	50	47,1	FI-SNV-35L-V-W3-DKO-GLA
	42	250	35	53	60	60	69,5	FI-SNV-42L-V-W3-DKO
	42	250	34	55,5	62,5	60	71,5	FI-SNV-42L-V-W3-DKO-GLA

Standard seal material is FKM (Viton®).

Straight Fitting with 24° Taper / O-Ring
Type FI-SNV ▪ Series S





Series	Tube OD mm D1	PN bar	Dimensions mm D2	L1	L2	S1	Weight kg ca. per 100	Ordering Codes
S	6	800	3	30,3	33	17	4,21	FI-SNV-06S-V-W3-DKO-GLB
	6	800	3	37	39,7	17	4,52	FI-SNV-06S-V-W3-DKO
	6	800	3	37,8	40,5	17	4,60	FI-SNV-06S-V-W3-DKO-GLA
	8	800	4	31,3	34	19	5,63	FI-SNV-08S-V-W3-DKO-GLB
	8	800	4	37	39,7	19	6,03	FI-SNV-08S-V-W3-DKO
	8	800	4	37,8	40,5	19	6,13	FI-SNV-08S-V-W3-DKO-GLA
	10	800	6	32,2	35	22	7,63	FI-SNV-10S-V-W3-DKO-GLB
	10	800	6	41	43,8	22	8,39	FI-SNV-10S-V-W3-DKO
	12	630	8	35,2	38	24	6,52	FI-SNV-12S-V-W3-DKO-GLB
	12	630	8	42	44,8	24	10,51	FI-SNV-12S-V-W3-DKO
	14	630	9	37,2	41	27	12,8	FI-SNV-14S-V-W3-DKO-GLB
	14	630	9	45	48,8	27	13,9	FI-SNV-14S-V-W3-DKO
	16	630	10	37,2	42	30	16,09	FI-SNV-16S-V-W3-DKO-GLB
	16	630	10	46	50,8	30	17,57	FI-SNV-16S-V-W3-DKO
	20	420	13	42	48	36	26,3	FI-SNV-20S-V-W3-DKO-GLB
	20	420	13	55	61	36	24,36	FI-SNV-20S-V-W3-DKO
	25	420	18	45,5	54,4	46	45,05	FI-SNV-25S-V-W3-DKO-GLB
	25	420	18	56,5	65,4	46	50,1	FI-SNV-25S-V-W3-DKO-GLA
	25	420	18	58	67	46	49,45	FI-SNV-25S-V-W3-DKO
	30	420	20	50	62	50	57,2	FI-SNV-30S-V-W3-DKO-GLB
	30	420	20	62	74	50	61,4	FI-SNV-30S-V-W3-DKO
	38	420	30	50	67	60	74,2	FI-SNV-38S-V-W3-DKO-GLB
	38	420	30	67	84	60	86,7	FI-SNV-38S-V-W3-DKO

Standard seal material is FKM (Viton®).

Ordering Codes

***FI-SNV*-10*S*-V*-W3*-DKO**

* Straight Fitting with 24° Taper / O-Ring (DKO)		**FI-SNV**
* Outside Tube Diameter D1 (in mm)		**-10**
* Series	Light Series (page 138)	**L**
	Heavy Series (page 139)	**S**
* Seal Material	FKM (Viton®)	**-V**
* Material Code	Steel, zinc/nickel-plated	**-W3**
Please contact STAUFF for alternative materials and surface finishings.		
* Assembling / Kitting	Fitting body supplied with swivel nuts and O-rings	**-DKO**
* Total length	dimension see table	**-GLA**
	dimension see table	**-GLB**

Spare Parts / Accessories



O-Ring
Type **O-RING** Page 239

H