

Equal Cross
Type FI-K ▪ Series LL / L / S







D

Ordering Codes

FI-K-10*L*-W3*-MS

* Equal Cross		**FI-K**
* Outside Tube Diameter D1 (in mm)		**-10**
* Series	Extra-Light Series	**LL**
	Light Series	**L**
	Heavy Series	**S**
* Material Code	Steel, zinc/nickel-plated	**-W3**
	Please contact STAUFF for alternative materials and surface finishings.	
* Assembling / Kitting	Fitting body only	**—**
	Fitting body supplied with cutting rings and union nuts	**-MS**
	Fitting body supplied with soft-sealing cutting rings and union nuts	**-MSV**

Connecting Parts


Cutting Ring
Type **FI-DS** Page 28


Soft-Sealing Cutting Ring
Type **FI-WDDS** Page 29


Support Sleeve
Type **FI-VH** Page 31


STAUFF Form EVO Sealing Ring
Type **FI-FD** Page 32


Union Nut
Type **FI-M** Page 33


37° Flared Tube Fitting Set
Type **FI-AB** Page 37

Series	Tube OD mm D1	PN bar	Dimensions mm D2	L	L1[1]	L2	S1	S2	Weight kg ca. per 100	Ordering Codes[3]
LL	4	100	3	15	21	11	9	10	1,68	**FI-K-04LL-W3**
	6	100	4,5	15	21	9,5	9	12	1,76	**FI-K-06LL-W3**
	8	100	6	17	23	11,5	12	14	2,85	**FI-K-08LL-W3**
L	6	500	4	19	27	12	12	14	3,40	**FI-K-06L-W3**
	8	500	6	21	29	14	12	17	3,93	**FI-K-08L-W3**
	10	500	8	22	30	15	14	19	5,01	**FI-K-10L-W3**
	12	400	10	24	32	17	17	22	6,90	**FI-K-12L-W3**
	15	400	12	28	36	21	19	27	12,36	**FI-K-15L-W3**
	18	400	15	31	40	23,5	24	32	17,40	**FI-K-18L-W3**
	22	250	19	35	44	27,5	27	36	22,60	**FI-K-22L-W3**
	28	250	24	38	47	30,5	36	41	35,60	**FI-K-28L-W3**
	35	250	30	45	56	34,5	41	50	54,67	**FI-K-35L-W3**
	42	250	36	51	63	40	50	60	92,70	**FI-K-42L-W3**
S	6	800	4	23	31	16	12	17	5,79	**FI-K-06S-W3**
	8	800	5	24	32	17	14	19	7,91	**FI-K-08S-W3**
	10	800	7	25	34	17,5	17	22	10,13	**FI-K-10S-W3**
	12	630	8	29	38	21,5	17	24	13,59	**FI-K-12S-W3**
	14	630	10	30	40	22	19	27	16,21	**FI-K-14S-W3**
	16	630	12	33	43	24,5	24	30	22,15	**FI-K-16S-W3**
	20	420	16	37	48	26,5	27	36	31,07	**FI-K-20S-W3**
	25	420	20	42	54	30	36	46	53,00	**FI-K-25S-W3**
	30	420	25	49	62	35,5	41	50	84,30	**FI-K-30S-W3**
	38	420	32	57	72	41	50	60	135,10	**FI-K-38S-W3**

[1] Approximate dimension in assembled condition.
[2] Weight excluding cutting rings and union nuts.
[3] Standard scope of delivery: Fitting body only.