

Blanking Plug with 24° Taper / O-Ring (DKO)
Type FI-VD ▪ Series L / S







Ordering Codes

***FI-VD*-15*L*-V*-W3*-M**

* Blanking Plug with 24° Taper / O-Ring (DKO)		**FI-VD**
* Outside Tube Diameter D1 (in mm)		**-15**
* Series	Light Series	**L**
	Heavy Series	**S**
* Seal Material	FKM (Viton®)	**-V**
* Material Code	Steel, zinc/nickel-plated	**-W3**
	Please contact STAUFF for alternative materials and surface finishings.	
* Assembling	Blanking plug only	**—**
	Blanking plug assembled with union nut	**-M**

Connecting Parts



Union Nut
Type **FI-M** Page 33

Spare Parts / Accessories



O-Ring
Type **O-RING** Page 239

Series	Tube OD mm D1	PN bar	Dimensions mm L1[1]	S1	Weight kg ca. per 100	Ordering Codes[3] Blanking plug only	Ordering Codes Blanking plug with union nut
L	6	800	16,5	14	0,57	FI-VD-06L/S-V-W3	FI-VD-06L-V-W3-M
	8	800	16,5	17	0,90	FI-VD-08L/S-V-W3	FI-VD-08L-V-W3-M
	10	800	17	19	1,37	FI-VD-10L/S-V-W3	FI-VD-10L-V-W3-M
	12	630	17	22	1,88	FI-VD-12L/S-V-W3	FI-VD-12L-V-W3-M
	15	400	18	27	3,00	FI-VD-15L-V-W3	FI-VD-15L-V-W3-M
	18	400	18,5	32	4,36	FI-VD-18L-V-W3	FI-VD-18L-V-W3-M
	22	250	19,3	36	6,52	FI-VD-22L-V-W3	FI-VD-22L-V-W3-M
	28	250	19,7	41	10,45	FI-VD-28L-V-W3	FI-VD-28L-V-W3-M
	35	250	23,2	50	19,66	FI-VD-35L-V-W3	FI-VD-35L-V-W3-M
	42	250	23,2	60	27,73	FI-VD-42L-V-W3	FI-VD-42L-V-W3-M
S	6	800	16,5	17	0,57	FI-VD-06L/S-V-W3	FI-VD-06S-V-W3-M
	8	800	16,5	19	0,90	FI-VD-08L/S-V-W3	FI-VD-08S-V-W3-M
	10	800	17	22	1,37	FI-VD-10L/S-V-W3	FI-VD-10S-V-W3-M
	12	630	17	24	1,88	FI-VD-12L/S-V-W3	FI-VD-12S-V-W3-M
	14	630	19	27	2,78	FI-VD-14S-V-W3	FI-VD-14S-V-W3-M
	16	630	19	30	3,54	FI-VD-16S-V-W3	FI-VD-16S-V-W3-M
	20	420	23,3	36	6,97	FI-VD-20S-V-W3	FI-VD-20S-V-W3-M
	25	420	24,2	46	10,94	FI-VD-25S-V-W3	FI-VD-25S-V-W3-M
	30	420	25,4	50	16,34	FI-VD-30S-V-W3	FI-VD-30S-V-W3-M
	38	420	26,7	60	27,11	FI-VD-38S-V-W3	FI-VD-38S-V-W3-M

[1] Approximate dimension in assembled condition.
[2] Weight excluding union nut.
[3] Standard scope of delivery: Blanking plug only.

Standard seal material is FKM (Viton®).